

CATEGORY	QUESTION	ANSWER
GENERAL SYSTEM INFORMATION	12 VDC OR 24VDC OPERATION:	_____
	CLASS "A" OR CLASS "B" CIRCUITS:	_____
	HARDWIRED OR ADDRESSABLE:	_____
	OCCUPANCY CLASSIFICATION:	_____
	VOICE EVACUATION, (YES OR NO)	_____
	STANDBY REQUIREMENTS, (24 OR 60 HOURS)	_____
	INTEGRAL COMMUNICATOR:	_____
INITIATION DEVICE CIRCUITS (IDC)	NUMBER OF ALARM CIRCUITS:	_____
	NUMBER OF SPRINKLER SUPERVISORY CIRCUITS:	_____
	NUMBER OF WATERFLOW CIRCUITS:	_____
	TOTAL IDC'S:	_____
NOTIFICATION APPLIANCE CIRCUITS (NAC)	NUMBER OF AUDIBLE CIRCUITS:	_____
	NUMBER OF VISUAL CIRCUITS:	_____
	TOTAL NAC'S:	_____
VOICE EVACUATION REQUIREMENTS	NUMBER OF SPEAKER CIRCUITS:	_____
	NUMBER OF FIRE PHONE CIRCUITS:	_____
	AMPLIFIER RATING:	_____
	PAGING MICROPHONE, (YES OR NO)	_____
	REMOTE MICROPHONE, (YES OR NO)	_____
	DIGITAL MESSAGE REPEATER, (YES OR NO)	_____
CONTROL CIRCUITS	MAGNETIC DOOR:	_____
	ELEVATOR RECALL:	_____
	AHU/FAN SHUTDOWN:	_____
	TOTAL CONTROL CIRCUITS:	_____
SMOKE DETECTORS	PHOTOELECTRIC OR IONIZATION:	_____
	2 OR 4-WIRE OPERATION:	_____
	INTEGRAL THERMAL, (YES OR NO):	_____
	AUXILIARY RELAY, (YES OR NO):	_____
DUCT SMOKE DETECTORS	PHOTOELECTRIC OR IONIZATION:	_____
	2 OR 4-WIRE OPERATION:	_____
	24/120/240 VOLT OPERATION:	_____
	DUCT SIZE/SAMP TUBE LENGTH:	_____
	REMOTE INDICATOR/TEST STATION:	_____
BEAM SMOKE DETECTORS	12VDC OR 24VDC OPERATION:	_____
	REMOTE INDICATOR/TEST STATION:	_____
HEAT DETECTORS	135° OR 194° TYPE:	_____
	AUXILIARY CONTACT/NUMBER OF CIRCUITS:	_____
	FIXED TEMPERATURE:	_____
	RATE OF RISE:	_____
	FIXED TEMPERATURE/RATE OF RISE:	_____
MANUAL PULL STATIONS	SURFACE OR SEMI-FLUSH MOUNTING:	_____
	SINGLE OR DOUBLE ACTION:	_____
	AUXILIARY CONTACT, (YES OR NO):	_____
	BREAKGLASS, (YES OR NO):	_____
	CODED OR NONCODED:	_____
	PRESIGNAL, (YES OR NO):	_____
AUDIBLE NOTIFICATION APPLIANCES	WALL OR CEILING MOUNT:	_____
	WEATHERPROOF, (YES OR NO):	_____
	DBA RATING:	_____
	BOX TYPE, (4" x 4" OR 1-GANG):	_____
VISUAL NOTIFICATION APPLIANCES	WALL OR CEILING MOUNT:	_____
	BOX TYPE, (4" x 4" OR 1-GANG):	_____
	CANDELA, (15, 30, 15/75, 75 OR 110cd)	_____

Always check local fire codes.

Central Alarm Inc. || For Systems Sales and Support, call 888-592-5276 || www.centralalarminc.com